

CONSTRUCTION NOTES

1. PARKING BARRIERS SHALL BE PLACED TO RESTRICT VEHICULAR ACCESS ON DISTURBED SOIL AREAS

BOULDERS:

BOULDERS SHALL BE GREATER THAN 18" DIAMETER AND BE KEYED IN TO THE SOIL A MINIMUM OF 6"

POSTS:

WOOD POSTS SHALL BE A MINIMUM OF 2' ABOVE GRADE, AND ANCHORED IN A CONCRETE FOOTING

SHRUBS OR WELL ESTABLISHED VEGETATION:





THIS PARKING BARRIER IS NOT RECOMMENDED IN AREAS USED FOR SNOW STORAGE

FENCING

POSTS SHALL BE ANCHORED IN A CONCRETE FOOTING.

2. INFORMATION ON REHABILITATING DISTURBED SOIL AREAS CAN BE FOUND ON THE NRCS "DIRECT SEEDING OF DISTURBED AREAS" TIP SHEET.
3. REGULARLY SCHEDULED MAINTENANCE INCLUDING SERVICE, REPAIR, OR REPLACEMENT OF COMPONENTS IS NECESSARY TO MAINTAIN FULL FUNCTION

TYPICAL PARKING BARRIERS

 <p>BOULDERS</p>	 <p>SHRUBS OR WELL ESTABLISHED VEGETATION</p>
 <p>WOOD POSTS</p>	<p>FENCING</p> 

U.S. DEPARTMENT OF AGRICULTURE NATURAL RESOURCES CONSERVATION SERVICE <small>IN COOPERATION WITH</small> TAHOE RESOURCE CONSERVATION DISTRICT, AND NEVADA TAHOE CONSERVATION DISTRICT			
DRAWN BY:	DATE	APPROVED BY:	DATE
SKB	8-18-06		

THIS SPECIFICATION IS BASED ON A REFERENCE TO THE NRCS STANDARD PRACTICE 561 - HEAVY USE AREA PROTECTION SYSTEMS. USERS OF THESE DRAWINGS AND ASSOCIATED INFORMATION SHALL BE QUALIFIED PERSONNEL, TRAINED TO INTERPRET AND ADAPT TECHNOLOGY ACCORDING TO LOCAL CONDITIONS.